



FLOORING

PRODUCT RANGE 2021



Adhesives
Primers
Sealers
Tapes

**TRADIES
TRUST**



TEXTILE FLOORING ADHESIVES

RANGE 2021

Adhesives
Pressure sensitive

**TRADIES
TRUST**

Textile Flooring Adhesives



Universal Pressure Sensitive Adhesive

Universal pressure sensitive adhesive

A solvent free pressure sensitive adhesive formulated for installing PVC backed, fibre backed, cushion back carpet tiles and reinforced vinyl composition tiles. For installing laminated slab underlays used in Double-Bond carpet installation. It can be applied to concrete substrates with moisture contents up to 95% Relative Humidity tested with the In- Situ Probe method and concrete substrates with pH readings of up to 12.0

ADVANTAGES

- Green Star Compliant
- Strong Initial Tack
- Solvent Free & low odour
- Anti-microbial Formulation

USES:

- Most types of vinyl composition tiles
- Laminated slab underlays used in Double-Bond carpet installation.

QUICK REF GUIDE

Coverage	5m²/L with V1 trowel 3m²/L with V2 trowel 8-10m²/L with roller
Area	Internal
Tack time	30min @ 20°C
Dry time	24 hours
Size- Code	15L 900140



Carpet Tile PS Adhesive

Solvent free pressure sensitive adhesive

RLA Carpet Tile PS Adhesive is a solvent free pressure sensitive adhesive formulated for installing PVC backed and modified composite backed Carpet Tiles. RLA Carpet Tile PS Adhesive can be applied to concrete substrates with moisture contents up to 95% relative humidity tested by way of In- Situ Probe method and concrete substrates with pH readings of up to 12.0.

ADVANTAGES

- High RH resistant
- Solvent Free & low odour
- Anti-microbial Formulation

USES:

- PVC backed, cushioned backed & modified composite backed carpet tiles.

QUICK REF GUIDE

Coverage	8-10m²/L with a long Nap roller
Area	Internal
Tack time	30min-1hour @ 20°C
Dry time	24 hours
Size- Code	15L - 900150



Carpet Adhesive

For both Double Bond and Direct Stick installations

Water-based carpet adhesive providing a strong tacky film of adhesive that is suitable for bonding carpets both Double Bond and Direct Stick installations. The adhesive offers a quick grab and has sufficient working time for smaller and larger installations. The adhesive tacks up quickly and has excellent re-bonding for hard to hold carpets.

ADVANTAGES

- Strong Initial Tack
- Water Based
- Installer Friendly

USES:

- Slab dual bond underlay
- Backed woven carpets
- Woven, jute sided & latex foam laminated slab underlays.

QUICK REF GUIDE

Coverage	3m²/L with V2 trowel 2m²/L with V3 trowel
Area	Internal
Tack time	5-10 minutes @ 20°C
Dry time	24 hours
Size - Code	15L - 900160



RL6000 Synthetic Grass Adhesive

All weather, solvent based adhesive

RL6000 Synthetic Grass Carpet Adhesive is an all-weather solvent based (flammable) adhesive specifically formulated for the outdoor installation of non-stretch open weave polypropylene backed synthetic grass carpet. It develops high strength quickly and when cured will withstand unfavorable weather conditions.

ADVANTAGES

- Develops high strength
- Good water resistance
- Exterior usage

USES:

- Synthetic Grass Carpet
- Indoor / Outdoor Carpets

QUICK REF GUIDE

Coverage	2m²/L with V3 trowel 1.2m²/L with V5 trowel
Area	Internal External
Tack time	5-10 minutes
Dry time	24 hours
Size- Code	20L - RL6000-20



Carpet Latex Adhesive

Compounded latex adhesive

RLA Carpet Latex is a compounded latex product used for the sealing of raw edges, strengthening worn backing, replacing damaged nap and adhering pad underlays to Subfloors.

ADVANTAGES

- Water based
- Rollable / Brushable
- Fast drying

USES:

- Domestic underlays
- Sealing selvage
- Worn backing

QUICK REF GUIDE

Area **Internal**
 Dry time **4-5 hours**
 Size - Code **5L - 900170**



RL1018 Fast Set

High quality PU adhesive

RL1018 is ideal for structural bonding where resistance to high temperatures and water is necessary. (confirms to Class D4-DIN EN 204).

ADVANTAGES

- High solids
- High strength
- Very economical
- Heat resistant

USES:

- Smoothedge, Gripper, Wood Products.
- Metal Trims, Nosings, Some ridged PVC

QUICK REF GUIDE

Area **Internal | External**
 Setting time **15 minutes**
 Dry time **24 hours**
 Size- Code **310ml - RL1018-310ml**



GS5 Seam Sealer

Water based

GS5 seam sealer is a solvent free, low odour, water based seam adhesive is designed to bond carpet seams together, once cured displays good water and heat resistance.

ADVANTAGES

- Heat/Water resistance
- Strong bond
- Australian made

USES:

- Bonding carpet edges together

QUICK REF GUIDE

Coverage **40-50 lineal meters**
 Area **Internal**
 Dry time **24 hours**
 Size - Code **1L - 900240**



RLA's carpet adhesives have been manufactured in Australia for over 50 years.



HEAT BOND TAPES

Release Tapes
Gold Foil Tapes
Dual Bond Tapes

**TRADIES
TRUST**



Economy Release Tape

Heat bond tape suitable for seaming woven and tufted carpet. Available in 100m rolls.

ADVANTAGES

- Easy to use
- Economical Solution

USES:

- Woven & tufted carpet

SIZE - CODE

100M - RLA121R



Premium Release Heat Bond Tape

Premium grade heat bond tape suitable for seaming woven and tufted carpet. Available in 100m rolls.

ADVANTAGES

- Easy to use
- Premium Grade

USES:

- Woven & tufted carpet

SIZE - CODE

100M - RLA135R



Gold Foil Tape

Low smoke low odour gold foil heat bond tape suitable for occupied commercial environments, suitable for woven and tufted carpets. Available in 100m rolls.

ADVANTAGES

- Easy to use
- Low smoke / low odour

USES:

- Woven & tufted carpet

SIZE - CODE

100M - RLA421R



Dual Bond Tape

Heat bond tape specifically designed for double-bond type of installations. Abundant adhesive and a wide fibre glass scrim makes it ideal for textured and woven carpets in commercial applications. Available in 100m rolls.

ADVANTAGES

- Easy to use
- Strong bond
- Wide fibre glass scrim

USES:

- Textured & woven carpet

SIZE - CODE

100M - RLA995R



TIMBER FLOORING ADHESIVES

PRODUCT RANGE 2021



MS Timber
SMP
Water based
Sealers

**TRADIES
TRUST**



MS Timber Flooring Adhesive

Isocyanate free permanently flexible adhesive

Permanently flexible solvent and isocyanate free MS timber flooring adhesive. For bonding approved acoustic underlays to most common subfloors. MS Timber Flooring Adhesive is also recommended for bonding solid timber flooring, Parquet flooring and engineered timber flooring to approved acoustic underlay as well as directly to most common subfloors.

ADVANTAGES

- Installer friendly
- Low VOC Emission
- Single part & permanently flexible
- Green tag certified

USES:

- Most types of timber floorcoverings.

QUICK REF GUIDE

Coverage	1-1.5m² depending on floorcovering.
Area	Internal
Tack time	30min @ 20°C
Dry time	24 hours
Size- Code	600ml - 620650 10L - 620653



RL1001

SMP Timber Flooring Adhesive

A single-part, permanently flexible, low VOC and isocyanate free timber flooring adhesive. For bonding approved acoustic underlays to most common subfloors. RL1001 is also recommended for bonding solid timber flooring, Parquet flooring and engineered timber flooring to approved acoustic underlay as well as directly to most common subfloors.

ADVANTAGES

- Installer friendly
- Low VOC Emission
- Single part & permanently flexible

USES:

- Most types of timber floorcoverings.

QUICK REF GUIDE

Coverage	1-1.5m² depending on floorcovering.
Area	Internal
Tack time	30min @ 20°C
Dry time	24 hours
Size- Code	15KG RL1001-15



HS Water Based Timber Adhesive

Specially designed for most types of timber floorcoverings

RLA HS is a high viscosity, high solids, trowellable, water-based vinyl acetate adhesive. For bonding Wood block and mosaic parquetry to timber substrates. It is also recommended for bonding Masonite, Plywood and Timber Sheeting underlayments to Timber and Concrete subfloors.

ADVANTAGES

- Non flammable
- Water based
- Easy to trowel and spread

USES:

- Wood block & mosaic parquetry
- Masonite, Plywood & Timber Sheeting underlayments

QUICK REF GUIDE

Coverage	1.5m²/L with V3 trowel
Area	Internal
Tack time	30min @ 20°C
Dry time	24 hours
Size- Code	15L - 900280



PU95

Polyurethane primer & green slab sealer

RLA PU 95 is moisture curing polyurethane primer and green slab sealer/ vapour barrier for cement-based substrates that are not subject to rising damp, or hydrostatic pressure. It can withstand a relative humidity moisture content up to 95% RH (ASTM F2170) it is a one component polyurethane primer/ green slab sealer that hardens and cures with the humidity present in the air and the substrate.

ADVANTAGES

- One component
- Solvent Free / Non flammable
- Moisture curing
- Excellent adhesion

USES:

- Internal use
- Porous & non porous substrates
- Freshly laid green concrete.

QUICK REF GUIDE

Coverage	200 grm/m² per coat
Area	Internal
Dry Time	2-24 hours
Size- Code	10kg - 620680



RESILIENT FLOORING ADHESIVES

PRODUCT RANGE 2021



MS Timber
SMP
Water based
Sealers

**TRADIES
TRUST**



Universal Resilient Flooring Adhesive

Universal Adhesive for a wide range of Floor Coverings.

An acrylic co-polymer hard set adhesive with strong initial tack and bond strength qualities for a range PVC vinyl and textile floorcoverings. It has excellent plasticiser resistance and non staining properties. It is for interior use only and is protected against bio-degradation, withstands normal wet cleaning practices and is suitable for use over underfloor heating installations.

ADVANTAGES

- Strong initial tack
- Low VOC Emission
- Green Star Compliant
- Solvent Free & Low odour
- Anti-microbial Formulation

USES:

- PVC Vinyl sheeting products.
- Vinyl composite tiles.
- PVC vinyl plank & tiles.
- Natural rubber up to 4mm.
- Linoleum.

QUICK REF GUIDE

Coverage	5m²/L with V1 trowel 3m²/L with V2 trowel 2m²/L with V3 trowel
Area	Internal
Tack time	5-10 minutes @ 20°C
Dry time	24 hours
Size- Code	15L - 900130



265 Universal Vinyl Adhesive

Excellent plasticiser resistance and nonstaining properties

RLA 265 is a water based acrylic emulsion with excellent plasticiser resistance and nonstaining properties. It is protected against bio-degradation, withstands normal wet cleaning practices and is suitable for use over underfloor heating installations.

ADVANTAGES

- High initial grab
- Excellent plasticiser resistance
- Non-staining
- Withstands wet cleaning practices.

USES:

- Domestic vinyl sheet.
- Commercial vinyl sheet.
- Hard to hold carpets.

QUICK REF GUIDE

Coverage	5m²/L with V1 trowel 3m²/L with V2 trowel
Area	Internal
Tack time	30min @ 20°C
Dry time	24 hours
Size - Code	15L - 900100



999 Multi-Purpose PS Adhesive

Solvent free pressure sensitive adhesive

RLA 999 Pressure Sensitive Adhesive is a solvent free pressure sensitive adhesive formulated for installing PVC backed, fibre backed, cushion back carpet tiles and reinforced vinyl composition tiles. It is also highly recommended for installing laminated slab underlays used in Double-Bond carpet installation.

ADVANTAGES

- Low VOC & Solvent free
- Green Star Compliant
- Anti-microbial Formulation
- Low Odour

USES:

- PVC, fibre & cushion back carpet tiles
- Reinforced vinyl composition tiles.

QUICK REF GUIDE

Coverage	5m²/L with V1 trowel 3m²/L with V2 trowel 8-10m²/L with a long Nap roller
Area	Internal
Tack time	30min @ 20°C
Dry time	24 hours
Size- Code	15L - 900110



Vinyl Plank Adhesive

Water based acrylic adhesive

RLA Vinyl plank adhesive is a solvent free, low odour, low VOC water based acrylic emulsion with excellent plasticiser resistance and non staining properties. It is protected against bio-degradation, withstands normal wet cleaning practices and is suitable for use over underfloor heating installations.

ADVANTAGES

- Green Star Compliant
- Strong Initial Tack
- Solvent Free
- Anti-microbial Formulation
- Low Odour

USES:

- Luxury vinyl plank.
- Luxury vinyl tile.

QUICK REF GUIDE

Coverage	5m²/L with V1 trowel 3m²/L with V2 trowel
Area	Internal
Tack time	5-10 minutes @ 20°C
Dry time	24 hours
Size- Code	15L - 900120

HT Vinyl Plank Adhesive

High temperature hard set adhesive



HT Vinyl plank is an acrylic polymer, high temperature hard set adhesive with a short open time and excellent adhesion. It is fibre – reinforced and highly shear- resistant with excellent plasticiser migration resistance, non staining properties and provides resistance to temperature variations.

ADVANTAGES

- High shear strength
- Green Star Compliant
- Resists temp. changes
- Solvent Free & Low odour
- Anti-microbial Formulation

USES:

- Luxury vinyl plank.
- Luxury vinyl tile.
- Bay windows.
- Areas exposed to direct sunlight.

QUICK REF GUIDE

Coverage	5m²/L with V1 trowel 3m²/L with V2 trowel
Area	Internal
Tack time	1-5 minutes @ 20°C
Dry time	24 hours
Size- Code	15L - 900125

RL1000 Resilient Flooring Adhesive

Isocyanate free water resistant, resilient flooring adhesive



A single-part, VOC compliant isocyanate free water resistant resilient flooring adhesive. For use in wet areas for bonding approved vinyl, rubber and linoleum floor coverings to most common internal and external subfloors. It is suitable for areas that are exposed to sun light.

ADVANTAGES

- VOC Compliant.
- Water resistant
- Withstands heat

USES:

- Vinyl floorcoverings
- Rubber floorcoverings

QUICK REF GUIDE

Coverage	3-4m²/L V1 trowel 2-2.5m²/L V2 trowel
Area	Internal/External
Tack time	30min @ 20°C
Dry time	24 hours
Size- Code	14KG - RL1000-14

Brushable Contact Adhesive

Rapid drying contact cement



RLA Brush Contact Adhesive is a high quality brushable grade solvent based (flammable), rapid drying contact cement, which has high strength, excellent ageing and heat resistance.

RLA Brush Contact Adhesive is designed for use on most types of vinyls, PVC skirtings/ extrusions, coverstrips, plastic and metal treads.

ADVANTAGES

- Rapid drying
- High strength
- Aging resistant
- Heat resistant

USES:

- Vinyl, PVC & Metal
- Decorative Laminates, MDF, wood & wood Veneer, paper honeycomb

QUICK REF GUIDE

Coverage	5-7m²/L spread rates depend on substrate consistency
Area	Internal
Initial dry time	5-10 minutes @ 20°C
Size- Code	4L 900210 20L - 900200

Sprayable Contact Adhesive

High quality contact adhesive



RLA Sprayable contact adhesive is a high quality solvent based contact adhesive designed for easy application by spraying to bond a wide range of materials It has excellent bond strength and high heat resistance. The high solids content gives outstanding economy of use.

ADVANTAGES

- High strength
- Very economical
- Heat resistant

USES:

- Vinyl, PVC & Metal
- Decorative Laminates, MDF, wood & wood Veneer, paper honeycomb

QUICK REF GUIDE

Coverage	6-8m²/L spread rates Depend on substrate Consistency
Area	Internal
Initial dry time	5-10 minutes @ 20°C
Size- Code	20L - 90020

TRADE TRUSTED ADVICE

The MyRLA app gives you instant access to a nationwide technical & sales force, at your fingertips. To help with project advice, product selection and job support.



MyRLA APP

Project & Product Advice
Usage calculators
Specification services
Data Sheet Downloads
Weekly prizes
& more

T. 1800 242 931

VIC

215 Colchester Rd
(PO Box 147)
Kilsyth VIC 3137

NSW

363 Wentworth Ave
Pendle Hill,
NSW 2145

QLD

57 Fulcrum Street
Richlands
QLD 4077

WA

24 Hanwell Way
Bassendean,
WA 6054

SA

30/32 Park Ave,
Woodville North
SA 5011

www.rlapolymers.com.au